

珠海华星龙企业有限公司

型号 Model NO.	压敏电压 Varistor Voltage	最大容许回路 电压 Max. Allowable Voltage (V)		最大限制电压 Max. Clamping Voltage	能量能耐 Energy (2ms)	最大峰值电流 Max. Peak Current (8/20 μs) (A)		电容量 (参考值) Capacitance (Reference) (1kHz)
	V _{1mA} (V)	AC _{rms}	DC	V _{150A} (V)	(J)	1time (A)	2time (A)	pF
MYL3A25K201	200 (180~220)	130	170	340	100	15000	10000	3200
MYL3A25K241	240 (216~264)	150	200	395	120	15000	10000	3000
MYL3A25K271	270 (243~297)	175	225	455	130	15000	10000	2800
MYL3A25K301	300 (270~330)	190	245	495	160	15000	10000	2500
MYL3A25K331	330 (297~363)	215	275	545	160	15000	10000	2100
MYL3A25K361	360 (324~396)	230	300	595	180	15000	10000	1850
MYL3A25K391	390 (351~429)	250	320	340	200	15000	10000	1500
MYL3A25K431	430 (387~473)	275	350	710	220	15000	10000	1250
MYL3A25K471	470 (423~517)	300	385	775	250	15000	10000	1100
MYL3A25K511	510 (459~561)	320	415	845	270	15000	10000	1000
MYL3A25K561	560 (504~616)	350	455	925	270	15000	10000	950
MYL3A25K621	620 (558~682)	380	505	1025	270	15000	10000	900
MYL3A25K681	680 (612~748)	420	560	1120	270	15000	10000	850
MYL3A25K751	750 (675~825)	460	615	1240	300	15000	10000	800
MYL3A25K781	780 (702~858)	510	670	1280	300	15000	10000	750
MYL3A25K821	820 (738~902)	550	745	1355	325	15000	10000	720
MYL3A25K911	910 (819~1001)	625	825	1500	360	15000	10000	680
	1000							
MYL3A25K102	(900~1100)	680	895	1650	400	15000	10000	650
	1100							
MYL3A25K112	(990~1201)	705	970	1815	440	15000	10000	600

珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路电压		最大限制电压	能量能耐	最大峰值电流		电容量（参考值）
	VaristoVoltage	Max.Allowable Voltage(V)		Max.Clamping Voltage	Enecgy (2ms)	Max.Peak Current(8/20 μ s) (A)		Capacitance (Reference) (1kHz)
	V _{1mA} (V)	AC _{rms}	DC	V _{150A} (V)	(J)	1time(A)	2time (A)	pF
MYL3A34K201	200(180~220)	130	170	340	200	25000	20000	6000
MYL3A34K241	240(216~264)	150	200	395	220	25000	20000	5800
MYL3A34K271	270(243~297)	175	225	455	240	25000	20000	5500
MYL3A34K301	300(270~330)	190	245	495	270	25000	20000	5300
MYL3A34K331	330(297~363)	215	275	545	300	25000	20000	5150
MYL3A34K361	360(324~396)	230	300	595	300	25000	20000	4700
MYL3A34K391	390(351~429)	250	320	340	330	25000	20000	4500
MYL3A34K431	430(387~473)	275	350	710	360	25000	20000	4200
MYL3A34K471	470(423~517)	300	385	775	360	25000	20000	3800
MYL3A34K511	510 (459~561)	320	415	845	390	25000	20000	3500
MYL3A34K561	560 (504~616)	350	455	925	390	25000	20000	3150
MYL3A34K621	620 (558~682)	380	505	1025	390	25000	20000	2800
MYL3A34K681	680 (612~748)	420	560	1120	400	25000	20000	2500
MYL3A34K751	750(675~825)	460	615	1240	440	25000	20000	2100
MYL3A34K781	780(702~858)	510	670	1280	440	25000	20000	1800
MYL3A34K821	820(738~902)	550	745	1355	500	25000	20000	1500
MYL3A34K911	910 (819~1001)	625	825	1500	550	25000	20000	1100
MYL3A34K102	1000 (900~1100)	680	895	1650	600	25000	20000	900
MYL3A34K112	1100(990~1210)	705	970	1815	650	15000	20000	850

珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路 电压		最大限制电压	能量能耐	最大峰值电流		电容量（参考值）
	Var i toVoltage	Max. Allowable		Max. Clamping	Enecgy	Max. Peak		Capacitance
		Voltage (V)		Voltage	(2ms)	Current (8/20; s) (A)		(Reference) (1kHz)
	V _{1mA} (V)	AC _{rms}	DC	V _{150A} (V)	(J)	1time (A)	2time (A)	pF
MYL3A40K201	200(180~220)	130	170	340	270	30000	20000	8000
MYL3A40K241	240(216~264)	150	200	395	300	30000	20000	7800
MYL3A40K271	270(243~297)	175	225	455	300	30000	20000	7500
MYL3A40K301	300(270~330)	190	245	495	330	30000	20000	7300
MYL3A40K331	330(297~363)	215	275	545	350	30000	20000	6800
MYL3A40K361	360(324~396)	230	300	595	350	30000	20000	6300
MYL3A40K391	390(351~429)	250	320	340	370	30000	20000	6000
MYL3A40K431	430(387~473)	275	350	710	400	30000	20000	5500
MYL3A40K471	470(423~517)	300	385	775	430	30000	20000	5000
MYL3A40K511	510 (459~561)	320	415	845	460	40000	25000	4700
MYL3A40K561	560 (504~616)	350	455	925	500	40000	25000	4450
MYL3A40K621	620 (558~682)	380	505	1025	550	40000	25000	4100
MYL3A40K681	680 (612~748)	420	560	1120	600	40000	25000	3700
MYL3A40K751	750(675~825)	460	615	1240	650	40000	25000	3500
MYL3A40K781	780 (702~858)	485	640	1280	650	40000	25000	3100
MYL3A40K821	820 (738~902)	510	670	1355	700	40000	25000	2700
MYL3A40K911	910 (819~1001)	550	745	1500	750	40000	25000	2450
MYL3A40K102	1000 (900~1100)	625	925	1650	800	40000	25000	2100
MYL3A40K112	1100 (990~1201)	680	895	1815	900	40000	25000	1700

珠海华星龙企业有限公司

型号 Model NO.	压敏电压	最大容许回路 电压		最大限制电压	能量能耐	最大峰值电流 Max. Peak Current(8/20; s) (A)		电容量 (参考值) Capacitance (Reference)(1kHz)
	Var i toVoltage	Max. Allowable Voltage(V)		Max. Clamping Voltage	Enecgy (2ms)	(A)		
	V _{1mA} (V)	AC _{rms}	DC	V _{150A} (V)	(J)	1time (A)	2time (A)	pF
MYL3A60K201	200(180~220)	130	170	340	450	50000	30000	16000
MYL3A60K241	240(216~264)	150	200	395	530	50000	30000	14500
MYL3A60K271	270(243~297)	175	225	455	550	50000	30000	12000
MYL3A60K301	300(270~330)	190	245	495	600	50000	30000	10500
MYL3A60K331	330(297~363)	215	275	545	650	50000	30000	9500
MYL3A60K361	360(324~396)	230	300	595	700	50000	30000	8300
MYL3A60K391	390(351~429)	250	320	340	880	50000	30000	7600
MYL3A60K431	430(387~473)	275	350	710	950	50000	30000	7000
MYL3A60K471	470(423~517)	300	385	775	1000	50000	30000	6500
MYL3A60K511	510 (459~561)	320	415	845	1100	50000	30000	5200
MYL3A60K561	560 (504~616)	350	455	925	1200	70000	45000	4500
MYL3A60K621	620 (558~682)	380	505	1025	1300	70000	45000	4000
MYL3A60K681	680 (612~748)	420	560	1120	1500	70000	45000	3600
MYL3A60K751	750(675~825)	460	615	1240	1500	70000	45000	3100
MYL3A60K781	780 (702~858)	485	640	1280	1600	70000	45000	2850
MYL3A60K821	820 (738~902)	510	670	1355	1800	70000	45000	2700
MYL3A60K911	910 (819~1001)	550	745	1500	2000	70000	45000	2500
MYL3A60K102	1000 (900~1100)	625	925	1650	2300	70000	45000	2300
MYL3A60K112	1100 (990~1201)	680	895	1815	2600	70000	45000	2000